

Leica Geosystems terrestrial laser scanners

Which laser scanner is right for you?



BLK360 SE



BLK360



RTC300



RTC500



RTC700

	BLK360 SE	BLK360	RTC300	RTC500	RTC700
Distance measurement system					
Maximum range	45 m	45 m	85 m	130 m	270 m
Maximum scan rate	340,000 pts/sec	680,000 pts/sec	1 mio pts/sec	2 mio pts/sec	2 mio pts/sec
Resolution settings	3 (6/12/25 mm @ 10 m)	4 (6/12/25/50 mm @ 10 m)	4 (3/6/12/25 mm @ 10 m)	4 (3/6/12/25 mm @ 10 m)	6 (0.8/1.6/3/6/12/25 mm @ 10 m)
Laser class	1	1	1	1	1
Laser wavelength	830 nm (invisible)	830 nm (invisible)	1550 nm (invisible)	1550 nm (invisible)	1550 nm (invisible)
Tilt sensor, Tilt accuracy	IMU	IMU	Tilt compensator, 3 arcsec	Tilt compensator, 3 arcsec	Tilt compensator, 3 arcsec
3D accuracy	4 mm @ 10 m 8 mm @ 20 m	4 mm @ 10 m 8 mm @ 20 m	1.5 mm @ 10 m 3.8 mm @ 50 m	1.5 mm @ 10 m 3.8 mm @ 50 m	1.5 mm @ 10 m 3.8 mm @ 50 m
Imaging system					
Internal camera	13 MP 4-camera system 104 MP per setup	13 MP 4-camera system 104 MP per setup	12 MP 6-camera system 432 MP per setup	12 MP 6-camera system 432 MP per setup	12 MP 6-camera system 432 MP per setup
HDR	5 brackets	5 brackets	5 brackets	5 brackets	5 brackets
Image acquisition time (HDR)	20 sec	20 sec	30 sec	30 sec	30 sec
Environmental					
Operating temperature	0°C to +40°C	0°C to +40°C	-20°C to +50°C	-20°C to +50°C	-20°C to +50°C
Solid particle, liquid ingress protection	IP54	IP54	IP55	IP55	IP55
Survey / setup functionality					
Known backsight	✗	✗	✗	✗	✓
Setup over a known point	✗	✗	✗	✗	✓
Resection	✗	✗	✗	✗	✓
Traverse	✗	✗	✗	✗	✓
Target measurements up to 75 m	✗	✗	✗	✗	✓
Targets from a full dome scan	✓	✓	✓	✓	✓
Onsite registration					
On-site automatic registration	✗	✓	✓	✓	✓
In-field cloud-to-cloud registration	✓	✓	✓	✓	✓
In-field target-based registration	✓	✓	✓	✓	✓
Cloud collaboration / Livelink					
Real-time interconnectivity between field and office	✗	✗	✓	✓	✓
Real-time interconnectivity in field between users	✗	✗	✓	✓	✓
Remote project and work coordination between multiple scanners	✗	✗	✓	✓	✓
General functionality					
Automatic self-calibration	✗	✗	✓	✓	✓
One button scan control	✓	✓	✓	✓	✓
Area scan	✗	✗	✗	✗	✓
Remote control	✓	✓	✓	✓	✓
Upgradeability					
Upgrade options	✗	✗	✓	✓	✗
Additional sensors					
IMU	✓	✓	✓	✓	✓
GNSS	✗	✗	✓	✓	✓
Visual Inertial System (VIS)	✗	✓	✓	✓	✓
Portability					
Weight	0.85 kg	0.85 kg	5.6 kg	5.6 kg	5.6 kg
Size	80 x 80 x 155 mm	80 x 80 x 155 mm	121 mm x 240 mm x 254 mm	121 mm x 240 mm x 254 mm	121 mm x 240 mm x 254 mm

✓ = Available, ✗ = Not available